



- NOTES:**
1. Total Panel Thickness (not including screws): 4.8mm ± 0.2mm
  2. Weight: 357.2g [12.6oz]
  3. Waterproof Rating: IP67
  4. All materials RoHS compliant
  5. Tape over all electrical connections

4mm Black Tape  
3mm Black Tape

Thread: 4-40  
Material: SS316  
Length: 7.9mm

**Wire #17**  
Length: 260mm  
Gauge: 22 AWG  
Color: Red

Plug: Waterproof Male Ø3.5xØ1.1mm



FILE DETAILS	SUBSTRATE	HARDWARE	POWER		
PRODUCT NAME: <b>9W 6V 221x257mm</b>	SIZE: 221x257mm	WIRE: Male 3.5x1.1mm 260mm	Spec. Tolerance: ±10% (Vp,Ip)		
DWG. NO. 9_9_221x257_R1	MATERIAL: 3.0mm AL-Plastic Composite	WIRE COLOR: Red	Cell Supplier: Solar World		
DWG. TYPE: Production	COLOR: Silver / Charcoal	WIRE NO. Wire 17	Cell: Effcell M C4 3BB 4.59W		
SCALE: UNITS: TOLERANCE: SHEET: 1:2.5 MM ±0.1mm 1/1	COATING: Urethane	STRAIN RELIEF: Metal	MC	12	pcs
CREATED BY: TK	DATE: 2017/7/19	SCREWS: C-MPSCRS028X0079-KM#	Voc	7.7	V
REV. CHANGE: DATE: CHK'D BY: 1 1 JC	TEMP. RANGE: -40°C - 85°C [-40°F - 185°F]	NUTS: None	Vp	6.5	V
			mAsc	1,520	mA
			mAp	1,420	mA
			Wp	9.2	W

This document contains proprietary information and should not be copied or shared without the consent of Voltaic Systems.