



NOTE:

- |   |  |
|---|--|
| <p>1 TOLERANCES UNLESS OTHERWISE SPECIFIED: <math>\pm 0.20</math></p> <p>2 ALL DIMENSION ARE IN mm</p> <p>3 GLASS THICKNESS:<br/>FRONT -- 0.7<br/>BACK -- 0.7</p> <p>4 VIEWING ANGLE: 6 O'CLOCK</p> | <p>5 LCD TYPE: TN, TRANSMISSIVE, POSITIVE</p> <p>6 FLUID SPECIFICATION:<br/>MULTIPLEX LEVEL: STATIC<br/>DRIVING VOLTAGE (VOP): 5 V<br/>OPERATING TEMP: <math>-10^{\circ}\text{C}</math> TO <math>60^{\circ}\text{C}</math><br/>STORAGE TEMP: <math>-20^{\circ}\text{C}</math> TO <math>70^{\circ}\text{C}</math></p> <p>7 CONNECTOR: PIN</p> |
|---|--|

DALIAN GOOD DISPLAY CO., LTD

APPROVED BY	CHECKED BY	DRAWN BY
Fu Yishan	Du Huaizhi	Liang Jiayi
DESIGN MODEL : EDC7658 C3G		REV. B
CUSTOMER MODEL :		
DATE: 09.3.20	SCALE:	PAGE 1 OF 1