



P.C.Board Layout

**材质 Material:**

绝缘体 Insulator: Glass filled PBT UL94V-0 ,Black

接触件 Contacts: Brass

电镀层 Plating: Whole Gold plated over Nickel

**电气性能 Electrical Characteristics:**

接触电阻 Contact Resistance: 30mΩmax. at DC 100mA

绝缘电阻 Insulator Resistance: 1000MΩmin. at 500V DC

耐压 Withstanding Voltage: 1000V AC/rms 50Hz For 1 minute

工作电流 Current Rating: 2 AMP

使用温度范围 Operating Temperature: -40°C ~ +105°C

TITLE		PCB SOCKET 2.54mm(0.100")		GENERAL TOLERANCE		DRAWN BY		DATE		<b>DENK</b> DENG KE <b>CONNECTOR</b> ELECTRONICS CO., LTD <b>登科电子有限公司</b>	
		1*20pin加长针脚排母_D11.0mm		x. : ±0.3		CHECKED BY		DATE			
SERIES				x.x: ±0.2		APPROVED BY		DATE			
CUSTOMER P/N				ANGLE TOLERANCE		DRAWING NO.		SHEET		1 OF 1	
UNITS		mm		x. : ±2°		SHEET SIZE		A4		REV.	
SCALE		2:1		x.x: ±1°		A0		REV.		A0	
PROJECTION				x.xx: ±0.5°							