



P.C.Board Layout

**材质 Material:**

绝缘体 Insulator: Glass filled PBT UL94V-0 ,Black

接触件 Contacts: Brass

电镀层 Plating: Whole Gold plated over Nickel

**电气性能 Electrical Characteristics:**

接触电阻 Contact Resistance: 30mΩmax. at DC 100mA

绝缘电阻 Insulator Resistance: 1000MΩmin. at 500V DC

耐压 Withstanding Voltage: 1000V AC/rms 50Hz For 1 minute

工作电流 Current Rating: 2 AMP

使用温度范围 Operating Temperature: -40°C ~ +105°C

TITLE		PCB SOCKET 2.54mm(0.100")		GENERAL TOLERANCE		DRAWN BY		DATE		<b>DENK</b> DENG KE <b>CONNECTOR</b> ELECTRONICS CO., LTD 登科电子有限公司	
		1*20pin排母_H8.5_D3.2mm		x. : ±0.3 x.x: ±0.2 x.xx: ±0.1		CHECKED BY		DATE			
SERIES				ANGLE TOLERANCE		APPROVED BY		DATE		DRAWING NO.	
CUSTOMER P/N				x. : ±2° x.x: ±1° x.xx: ±0.5°						SHEET 1 OF 1	
UNITS		mm		PROJECTION						SHEET SIZE A4	
SCALE		2:1								REV. A0	
SCALE	DESCRIPTION	CHK	DATE	SCALE	2:1						