



P.C.B Layout

**材质 Material:**

绝缘体 Insulator: Glass filled PBT UL94V-0 ,Black

接触件 Contacts: Brass

电镀层 Plating: Whole Gold plated over Nickel

**电气性能 Electrical Characteristics:**

接触电阻 Contact Resistance: 30mΩmax. at DC 100mA

绝缘电阻 Insulator Resistance: 1000MΩmin. at 500V DC

耐压 Withstanding Voltage: 1000V AC/rms 50Hz For 1 minute

工作电流 Current Rating: 3 AMP

使用温度范围 Operating Temperature: -55°C ~ +105°C

				TITLE		GENERAL TOLERANCE		DRAWN BY		DATE		<b>DENK</b> DENG KE <b>CONNECTOR</b> ELECTRONICS CO., LTD <b>登科电子有限公司</b>	
				PIN HEADER 2.54mm (0.100 ")		x. : ±0.3		CHECKED BY		DATE			
				1*20pin直排针_L9.0_D3.0		x.x: ±0.2		APPROVED BY		DATE			
				SERIES		x.xx: ±0.1		DRAWING NO.		SHEET		1 OF 1	
				CUSTOMER P/N		ANGLE TOLERANCE		SHEET SIZE		A4		REV.	
				UNITS		x. : ±2°		A4		REV.		A0	
SCALE		DESCRIPTION		CHK		DATE		A4		REV.		A0	
SCALE		DESCRIPTION		CHK		DATE		A4		REV.		A0	